

APLearn: Machine Learning in APL

Borna Ahmadzadeh

borna.ahz@gmail.com

github.com/bobmcdear

About Me

- Third-year computer student at York University in Toronto, Canada
- Programming since second grade
- Passionate about artificial intelligence
- Experience in computer vision, NLP, and traditional data science
- APL outsider; perspective that of machine learning developer!





Path to APL




Haskell

*Programming beyond
imperative languages*



Foundations


*Type systems,
category theory, ...*



APL


*Notation as a tool of
thought*

Serendipity of Deep Learning & APL




Arrays

Input and parameters are multi-dimensional arrays.




Regular shapes

Data is neither jagged nor deeply nested.



Parallel Operations

Key operations include matrix multiplication, reductions, etc.



Conditional-free

Conditional statements and dynamic control flow are absent.


trap

GPT-like transformers in APL

```
1      :Namespace INF
2
3      MASK←-1E10×-(132)°.≥132
4      UNSQZ←{((ρω),1)ρω}
5      AVG←{UNSQZ (+/ω)÷-1↑ρω}
6
7      FWD←{
8          s←α
9          LN←{(α>s.BLN)+°1↑(α>s.WLN)×°1↑diff÷°1↑(1E-5+AVG 2*~diff←ω-°1↑AVG ω)*0.5}
10         MHSA←{
11             q k v←((α>s.BQKV)+°3↑ω+.×α>s.WQKV)°{0 2 1 3$ω[]°1↑α}~13
12             attn←{e÷°1↑UNSQZ+/e←*ω-°1↑UNSQZ[/ω]}MASK[12[]pq;12[]pk]+°2↑(q+.×°2↑$°2↑k)÷(-1↑pk)*0.5
13             (α>s.B0)+°1↑((ρω)ρ0 2 1 3$attn+.×°2↑v)+.×α>s.W0
14         }
15         MLP←{(α>s.B2)+°1↑({0.5×ω×1+7×0.797885×ω+0.044715×ω*3})(α>s.B1)+°1↑ω+.×α>s.W1)+.×α>s.W2}
16         BLK←{ind inp←ω ⋄ (ind+1) ({ω+ind MLP ω LN~1+2×ind})inp+ind MHSA inp LN~2×ind}
17         s.WH+.×~(2×#s.W1)LN 1>BLK*(#s.W1)↑0 (s.WPE[11[]ρω;]+°2↑s.WTE[ω;])
18     }
19
20     GEN←{inp cnt←ω ⋄ α{ω,(∘▽)°1↑-1↑[1]α FWD (-(#α.WPE)[1[]ρω)+[1]ω}*cnt↑inp}
21
22     :EndNamespace
```

What About Machine Learning?

- Linear models, decision trees, clustering, and more
- Unglamorous but effective, cheap, and simple
- Still dominant in key industries
- Heterogeneous algorithms without an overarching theme
- Conditional statements, iterative processes, graphs, ...




APLearn




Pre-processing

*Standardization,
categorical encoding,
and train-test splits*




Metrics

*Mean absolute and
squared errors,
accuracy, F1 score, ...*



Supervised

*Linear and logistic regression,
vector machines, random
forests, ...*



Unsupervised

*Dimensionality reduction
and clustering*

Design Principles

- Inspired by scikit-learn with a functional flavour
- Model and transformation states represented by record-like namespaces
- Consistent interface across `fit`, `pred`, and `trans`
- Built-in composability

Function	Role
<code>fit</code>	Learns state from data (α) given hyperparameters (ω).
<code>pred</code>	Makes predictions about data (α) using state (ω).
<code>trans</code>	Applies transformation to data (α) using state (ω).

```

1 ]Import # APLSource
2
3 # Reads data and moves target to first column for ease
4 (data header)←CSV 'adult.csv' 0 4 1
5 data header←(header⊖'income')⊖data header
6
7 # Encodes categorical features and target; target is now last
8 cat_names←'workclass' 'education' 'marital-status' 'occupation' 'relationship' 'race' 'gender' 'native-country'
9 data←data PREPROC.ONE_HOT.trans data PREPROC.ONE_HOT.fit header⊖cat_names
10 data←data PREPROC.ORD.trans data PREPROC.ORD.fit 0
11
12 # Creates 80:20 training-validation split and separates input & target
13 train val←data MISC.SPLIT.train_val 0.2
14 (X_t y_t) (X_v y_v)←(1+≠data) MISC.SPLIT.xy~train val
15
16 # Normalizes data, trains, takes argmax of probabilities, and evaluates accuracy
17 X_t X_v←(X_t PREPROC.NORM.fit 0)∘(PREPROC.NORM.trans~)X_t X_v
18 st←X_t y_t SUP.LOG_REG.fit 0.01
19 out←0⊖1-X_v SUP.LOG_REG.pred st
20 ⊖y_v MISC.METRICS.acc out

```

```
1 # Loads data.
2 df = pd.read_csv('adult.csv')
3
4 # One-hot encodes categorical columns.
5 cat_cols = ['workclass', 'education', 'marital-status', 'occupation', 'relationship', 'race', 'gender', 'native-country']
6 df = pd.get_dummies(df, columns=cat_cols)
7
8 # Converts target variable from string into integer.
9 df['income'] = (df['income'] == '>50K').astype(int)
10
11 # Splits data into training and validation sets.
12 train, val = train_test_split(df, test_size=0.2, shuffle=True)
13
14 # Separates independent and dependent variables.
15 X_t, y_t = train.drop(columns=['income']), train['income']
16 X_v, y_v = val.drop(columns=['income']), val['income']
17
18 # Normalizes features.
19 scaler = StandardScaler()
20 X_t = scaler.fit_transform(X_t)
21 X_v = scaler.transform(X_v)
22
23 # Creates model, trains, makes predictions, and computes accuracy.
24 log_reg = LogisticRegression(C=1 / 0.01)
25 log_reg.fit(X_t, y_t)
26 log_reg_y_hat = log_reg.predict(X_v)
27 print(accuracy_score(y_v, log_reg_y_hat))
```

Advantages and Drawbacks

- Algorithms seamlessly mapped from paper to APL
- Free from software noise like classes, pointers, ...
- Codebase in one place—no Python + NumPy + Fortran
- Native functionality for statistics and data science

but...


- Difficult to switch from traditional imperative mindset
- Not as array-centric as deep learning
- Slower than scikit-learn; compilation not straightforward
- Smaller ecosystem

Future Directions


- Enhanced handling of trees
- Complete Co-*dfns* support
- Automatic differentiation
- Advanced solvers and backends
- Rigorous unit tests
- More idiomatic APL
- Better documentation

Pull requests and issues are appreciated and welcome!

Thank you for your time!



[linkedin.com/in/borna-ahmadzadeh](https://www.linkedin.com/in/borna-ahmadzadeh)



github.com/bobmcdear